

# Linear High Bay



## FEATURES

- > Lightweight aluminum frame
- > Dimmable
- > Options available with normal lead times: Integrated occupancy sensor, Plug and Play cord, or Hardwire cord
- > Clear or Frosted polycarbonate lens
- > Hanging cables included
- > IP20 rated for indoor use
- > In-series transient voltage surge suppressor (TVSS)
- > UL1598 Listed
- > Infrared motion sensor

## SPECIFICATIONS

Input Voltage ..... 120/277V  
 Performance ..... Up to 130 lm/W  
 Calculated Lifetime ..... 155,000 hours  
 Operational Temperature ..... -20°C (-4°F) - 50°C (122°F)  
 Distribution ..... 110°  
 Mount Type ..... Suspension, Surface Mount  
 Available Wattages ..... 100W, 165W, 210W, 300W  
 Available Color Temperatures ..... 4000K, 5000K  
 Available Lengths ..... 2 ft, 4 ft

## LUMINOUS OUTPUT

| Wattage | 4000K     | 5000K     |
|---------|-----------|-----------|
| 100W    | 12,355 lm | 12,710 lm |
| 165W    | 20,917 lm | 21,488 lm |
| 210W    | 25,673 lm | 26,299 lm |
| 300W    | 38,572 lm | 39,627 lm |



## ACCESSORIES

| Product Accessories   | Part Number     | Color                                 |
|---|-----------------|---------------------------------------|
| Stainless Steel Suspension Cables - 5 Ft                    | EPM-SC-05       |                                       |
| Stainless Steel Suspension Cables - 10 Ft                   | EPM-SC-10       |                                       |
| Stainless Steel 1/4" Thimble for Suspension Cable           | EPM-SC-TH-14-SS |                                       |
| Stainless Steel 3/8" Carabiner for Suspension Cable         | EPM-SC-SH-38-SS |                                       |
| Linear High Bay LED Battery Backup                          | EPM-LL-BB       |                                       |
| Linear High Bay LED Motion Sensor                           | EPM-LHB-MS      |                                       |
| Wireless Motion Sensor Lens 8' Height, up to 44' Diameter   | EPM-MS-L2       | <b>BK</b> - Black                     |
| Wireless Motion Sensor Lens 20' Height, up to 40' Diameter  | EPM-MS-L3       | <b>BR</b> - Brown<br><b>GR</b> - Gray |
| Wireless Motion Sensor Lens 40' Height, up to 100' Diameter | EPM-MS-L7       | <b>WH</b> -White                      |
| Wireless Motion Sensor Remote Control                       | EPM-HA-MS-R     |                                       |

## ORDERING INFORMATION

SAMPLE ORDER NUMBER: EPM-LHB-22-165-50-PR-1-PP - C

| Series                     | Product                   | Length           | Wattage    | Color Temp.                | Premium      | Input Voltage | Fixture Disconnect  | Motion Sensor   | Lens                     |
|----------------------------|---------------------------|------------------|------------|----------------------------|--------------|---------------|---|---|--------------------------|
| EPM - ePOWER Manufacturing | LHB - Linear High Bay LED | 12 - 1 Ft x 2 Ft | 100 - 100W | 40 - 40000K<br>50 - 50000K | PR - Premium | 1 - 120/277V  | PP - Plug-and- Play<br>HW - Factory Installed Hardwire Cord | (Blank) - No Motion Sensor<br>MS - with Motion Sensor | C - Clear<br>F - Frosted |
|                            |                           | 22 - 2 Ft x 2 Ft | 165 - 165W |                            |              |               |   |   |                          |
|                            |                           | 14 - 1 Ft x 4 Ft | 210 - 210W |                            |              |               |   |   |                          |
|                            |                           | 24 - 2 Ft x 4 Ft | 300 - 300W |                            |              |               |   |   |                          |
| EPM                        | LHB                       |                  |            |                            | PR           | 1             |   |   |                          |