

# Linear Retrofit Kit



## FEATURES

- > Adjusts from 4" to 5-1/4"
- > Made in the USA
- > Polycarbonate frosted and clear lens
- > Calculated lifetime L70 205,000 hours
- > Damp listed
- > UL1598C Classified
- > In-series transient voltage surge suppressor (TVSS)

## SPECIFICATIONS

Input Voltage ..... 120-277V  
 Performance..... Up to 145 lm/W  
 Operational Temperature..... 0°C to 45°C (32°F to 113°F)  
 Distribution..... 140°  
 Available Wattages..... 25W, 50W  
 Available Color Temperatures..... 3000K, 4000K, 5000K  
 Available Length..... 4ft



Frosted Lens Option



Clear Lens Option

## LUMINOUS OUTPUT

Wattage	4000K	5000K
25W	4,050 lm	4,050 lm
50W	7,129 lm	7,166 lm



\* All data is for clear lens

## ORDERING INFORMATION

SAMPLE ORDER NUMBER: EPM-LR-04-25-50-F

Series	Product	Size	Wattage	Color Temp.	Lens Opacity
EPM	LR – Linear Retrofit LED	04 - 4 Ft	25 - 25W	30 - 3000K	F - Frosted
			50 – 50W	40 - 4000K	C - Clear
EPM	LR	04			