

Linear Vapor Tight LED



FEATURES

- > Durable aluminum casing for optimal heat dissipation
- > Suspended or Surface mount the fixture
- > Includes 6' hardwired cord
- > Optional motion sensor
- > In-series transient voltage surge suppressor (TVSS)
- > UL1598 Listed

SPECIFICATIONS

Input Voltage 120/277V
 Performance Up to 110 lm/W
 Operational Temperature -20°C to 55°C (-4°F to 131°F)
 Distribution 120°
 Mount Type Suspended or Surface Mounted
 Available Wattages 24W, 30W, 40W, 50W, 60W
 Available Color Temperatures 3000K, 4000K, 5000K

ACCESSORIES

Installation Accessories	Part Number
Linear Vapor Tight Motion Sensor Remote	EPM-LL-VT-MS-R



LUMINOUS OUTPUT

Wattage	3000K	4000K	5000K
24W	2,482 lm	2,640 lm	2,640 lm
30W	2,919 lm	3,330 lm	3,330 lm
40W	4,088 lm	4,440 lm	4,440 lm
50W	5,259 lm	5,500 lm	5,500 lm
60W	6,185 lm	7,384 lm	7,615 lm

ORDERING INFORMATION

SAMPLE ORDER NUMBER: EPM-LL-VT-02-24-PF-30-PR-1-AA-MS

Series	Product	Type	Length	Wattage	Tube Opacity	Color Temp	Premium	Input Voltage	Color	Motion Sensor
EPM - ePOWER Manufacturing	LL - Linear LED	VT -Vapor Tight	02 - 2 Ft	24 - 24W 30 - 30W	PF - Frosted	30 - 3000K 40 - 4000K 50 - 5000K	PR - Premium	1 - 120/277V	AA - Anodized Aluminum WH - White	(blank) - No Motion Sensor MS - Motion Sensor
			04 - 4 Ft	40 - 40W 50 - 50W 60 - 60W						
EPM	LL	VT					PR	1		