

NCO Series <u>LED</u>

High Temperature & Standard Temperature Specifications

SPECIFICATIONS

Power Factor	>0.9
Input Voltage	120/277V & 347/480V
Performance	Up to 151 lm/W
Operational Temperature	40°F to 195°F (-40°C to 90°C)
Distribution	120°, 60° & Aisle
Mount Type	Suspension
Kelvin Temperature	4000K, 5000K
Available Wattages 100W, 1	50W, 200W, 250W, 300W, 400W
!	500W, 600W, 700W, 800W, 900W
Color Rendering Index (4000)	<)>70
Color Rendering Index (5000)	<)>90

FEATURES

- > Available in high temperature (up to 195°F) or standard temperature (up to 130°F)
- > Inventronics Drivers with less than 1% failure rate
- > Patent-pending design extends fixture life by helping prevent build-up of insulating dust and debris and eliminates illumination dead spots
- > Patent-pending remote driver minimizes fixture operating temperature without re-gridding required
- > Includes 10 Year Module Warranty
- > Dimmable 0-10V
- > In-series transient voltage surge suppressor (TVSS) protects fixture against failure due to power supply surges
- > Optional motion sensor. Choose from standard by Wattstopper with L7 lens (fig 1.1 & 1.2*), or Internet of Things (IOT) by Enlighted Sensors (fig 1.3).

> UL 1598 listed

> IP65 rated











LUMINOUS OUTPUT & DIMENSIONS

WATTAGE	LUMENS	LENGTH		
100 Watts	12,960 lumens	18 inches		
150 Watts	21,600 lumens	26 inches		
200 Watts	31,070 lumens	34 inches		
250 Watts	36,000 lumens	42 inches		
300 Watts	44,020 lumens	50 inches		
400 Watts	57,600 lumens	66 inches		
500 Watts	72,000 lumens	82 inches		
600 Watts	86,400 lumens	98 inches		
700 Watts	100,800 lumens	114 inches		
800 Watts	115,200 lumens	130 inches		
900 Watts	129,600 lumens	146 inches		

POWER CORD (REQUIRED)

	<u>-</u>
DESCRIPTION	PRODUCT NUMBER
125V, 15 amp, Straight Blade, 6 ft	PC-PP-125-15-SB-6
125V, 15 amp, Straight Blade, 12 ft	PC-PP-125-15-SB-12
125V, 15 amp, Twist Lock, 6 ft	PC-PP-125-15-TL-6
125V, 15 amp, Twist Lock, 12 ft	PC-PP-125-15-TL-12
125V, 20 amp, Twist Lock, 6 ft	PC-PP-125-20-TL-6
125V, 20 amp, Twist Lock, 12 ft	PC-PP-125-20-TL-12
250V, 20 amp, Twist Lock, 6 ft	PC-PP-250-20-TL-6
250V, 20 amp, Twist Lock, 12 ft	PC-PP-250-20-TL-12
277V, 15 amp, Twist Lock, 6 ft	PC-PP-277-15-TL-6
277V, 15 amp, Twist Lock, 12 ft	PC-PP-277-15-TL-12
277V, 20 amp, Twist Lock, 6 ft	PC-PP-277-20-TL-6
277V, 20 amp, Twist Lock, 12 ft	PC-PP-277-20-TL-12
480V, 20 amp, Twist Lock, 6 ft	PC-PP-480-20-TL-6
480V, 20 amp, Twist Lock, 12 ft	PC-PP-480-20-TL-12
600V, 20 amp, Twist Lock, 6 ft	PC-PP-600-20-TL-6
600V, 20 amp, Twist Lock, 12 ft	PC-PP-600-20-TL-12
600V, Whip, 12ft	PC-PP-600-W-12

^{*}All Motion sensor purchases come as a set, including a motion sensor and an L7 Wattstopper lens.

NCO ORDERING INFORMATION

SAMPLE ORDER NUMBER: NCO-3-100-40-1-2-1-1-1-X-X-1

SERIES	WATTAGE	KELVIN	OPTICS	LENS	FINISH	DRIVER VOLTAGE	REMOTE CABLE	MOTION SENSOR	BATTERY BACKUP	DLC
NCO-3 High Temp	100- (100W)	40- (4000K)	1- No Optics	2- Flat Poly Clear	1- Black	1- 120/277V	1- 3'	X- No	X- No	1- Standard
NCO-4 Std Temp	150- (150W)	50- (5000K)	2- 60°	6- Flat tempered glass clear		4- 347/480V	2- 10'	1- Standard*	1- Yes	2- Premium
	200- (200W)		4- Aisle				3- 25'	2- Internet of Things*		
	250- (250W)						4- 50'			
	300- (300W)						5- 100'			
	400- (400W)						6- 150'			
	500- (500W)						7- 200'			
	600- (600W)						8- 250'			
	700- (700W)									
	800- (800W)									
	900- (900W)									

^{*} Motion Sensor information: Standard (1) features sensors by Wattstopper with L7 lens. Internet of Things or IOT, (2) features sensors by Enlighted Sensors

^{**} Fixture includes a 6 foot Whip Plug N Play Cord. For additional cord options, please see Power Cord Table above for ordering information.






NCO Series LED Filled with Bright Ideas for Improving Lighting Reliability

Optics Information


NO OPTICS

> Great for general illumination. No Optics are also great if you want to maximize horizontal light & to achieve uniform lighting overall. Ideal for 30 feet and below.



60 DEGREE OPTICS

> Great for higher ceilings. Best used for fixtures mounted 30+ feet up. (This image captures a 25 foot mounting height).



AISLE OPTICS

> Great for racking. With Aisle Optics, light is not wasted in ajoining aisles. This means you can reduce the number of fixtures in your facility, or can substantially reduce wattage when switching from HID or Flourescents to LED.

