



# Turret Series LED

## Standard Temperature Specifications

### SPECIFICATIONS

Power Factor.....	>0.9
Input Voltage .....	120/277V & 347/480V
Performance.....	Up to 163 lm/W
Operational Temperature.....	-40°F to 125°F (-40°C to 52°C)
Distribution.....	120°
Mount Type.....	Suspension
Available Wattages.....	100W, 150W, 200W, 250W, 300W
Kelvin Temperature .....	4000K, 5000K
Color Rendering Index (4000K) .....	>70
Color Rendering Index (5000K) .....	>90

### FEATURES

- > Patent-pending remote driver minimizes fixture operating temperature and allows fixture to evolve with changing plant floor demands with no re-gridding required
- > Inventronics Drivers with less than 1% failure rate
- > Dimmable 0-10V
- > In-series transient voltage surge suppressor (TVSS) protects fixture against failure due to dirty power and power supply surges
- > Includes 10 Year Module Warranty
- > Operational Temperature up to 125°F (52°C)
- > Optional motion sensor. Choose from standard by Wattstopper with L7 lens (fig 1.1 & fig 1.2\*), or Internet of Things (IOT) by Enlighted Sensors (fig 1.3).
- > UL 1598 listed
- > IP65 rated



### LUMINOUS OUTPUT

WATTS	LUMENS
100 Watts	14,400 lumens
150 Watts	22,180 lumens
200 Watts	32,730 lumens
250 Watts	39,910 lumens
300 Watts	49,550 lumens

### POWER CORDS & ACCESSORIES

DESCRIPTION	PRODUCT NUMBER
125V, 15 amp, Straight Blade, 6 ft	PC-PP-125-15-SB-6
125V, 15 amp, Straight Blade, 12 ft	PC-PP-125-15-SB-12
125V, 15 amp, Twist Lock, 6 ft	PC-PP-125-15-TL-6
125V, 15 amp, Twist Lock, 12 ft	PC-PP-125-15-TL-12
125V, 20 amp, Twist Lock, 6 ft	PC-PP-125-20-TL-6
125V, 20 amp, Twist Lock, 12 ft	PC-PP-125-20-TL-12
250V, 20 amp, Twist Lock, 6 ft	PC-PP-250-20-TL-6
250V, 20 amp, Twist Lock, 12 ft	PC-PP-250-20-TL-12
277V, 15 amp, Twist Lock, 6 ft	PC-PP-277-15-TL-6
277V, 15 amp, Twist Lock, 12 ft	PC-PP-277-15-TL-12
277V, 20 amp, Twist Lock, 6 ft	PC-PP-277-20-TL-6
277V, 20 amp, Twist Lock, 12 ft	PC-PP-277-20-TL-12
480V, 20 amp, Twist Lock, 6 ft	PC-PP-480-20-TL-6
480V, 20 amp, Twist Lock, 12 ft	PC-PP-480-20-TL-12
600V, 20 amp, Twist Lock, 6 ft	PC-PP-600-20-TL-6
600V, 20 amp, Twist Lock, 12 ft	PC-PP-600-20-TL-12
600V, Whip, 12ft	PC-PP-600-W-12
Turret Hub Hanger 0.5" Male	1278-5-M
Turret Hub Hanger 0.75" Male	1278-75-M
Turret Hub Hanger 0.5" Female	1278-5-F
Turret Hub Hanger 0.75" Female	1278-75-F

\*All Motion sensor purchases come as a set, including a motion sensor and an L7 Wattstopper lens.

### TURRET ORDERING INFORMATION

SERIES	WATTAGE	KELVIN	OPTICS	LENS	FINISH	DRIVER VOLTAGE	REMOTE CABLE	MOTION SENSOR	BATTERY BACKUP	DLC
TUR-6 Std Temp	100- (100W)	40- (4000K)	1- No	2- Flat Poly Clear	1- Black	1- 120/277V	1- 3'	X- No	X- No	1- Standard
	150- (150W)	50- (5000K)		6- Flat Tempered Glass Clear		4- 347/480V	2- 10'	1- Standard*	1- Yes	2- Premium
	200- (200W)						3- 25'	2- Internet of Things*		
	250- (250W)						4- 50'			
	300- (300W)						5-100'			
							6- 150'			
							7- 200'			
							8- 250'			

\* Motion Sensor information: Standard (1) features sensors by Wattstopper with L7 lens. Internet of Things or IOT, (2) features sensors by Enlighted Sensors

\*\* Fixture includes a 6 foot Whip Plug N Play Cord. For additional cord options, please see the Power Cord Table referenced above for ordering information.

3115 N 21<sup>st</sup> Street, Suite 2, Sheboygan, WI 53083  
920-287-3840

tactiklighting.com





# Turret Series LED

## High Temperature Specifications

### SPECIFICATIONS

Power Factor.....	>0.9
Input Voltage .....	120/277V & 347/480V
Performance.....	Up to 163 lm/W
Operational Temperature.....	-40°F to 185°F (-40°C to 71°C)
Distribution.....	120°
Mount Type.....	Suspension
Available Wattages.....	100W, 150W, 200W, 250W, 300W
Kelvin Temperature .....	4000K, 5000K
Color Rendering Index (4000K) .....	>70
Color Rendering Index (5000K) .....	>90

### FEATURES

- > Patent-pending remote driver minimizes fixture operating temperature and allows fixture to evolve with changing plant floor demands with no re-gridding required
- > Inventronics Drivers with less than 1% failure rate
- > Dimmable 0-10V
- > In-series transient voltage surge suppressor (TVSS) protects fixture against failure due to dirty power and power supply surges
- > Includes 10 Year Module Warranty
- > Up to 185°F (85°C) at 60% light output, or up to 170°F (77°C) at 100% light output
- > Optional motion sensor. Choose from standard by Wattstopper with L7 lens (fig 1.1 & fig 1.2\*), or Internet of Things (IOT) by Enlighted Sensors (fig 1.3).
- > UL 1598 listed
- > IP65 rated



### LUMINOUS OUTPUT

WATTS	LUMENS
100 Watts	13,940 lumens
150 Watts	22,180 lumens
200 Watts	32,730 lumens
250 Watts	39,910 lumens
300 Watts	49,550 lumens

### POWER CORD & ACCESSORIES

DESCRIPTION	PRODUCT NUMBER
125V, 15 amp, Straight Blade, 6 ft	PC-PP-125-15-SB-6
125V, 15 amp, Straight Blade, 12 ft	PC-PP-125-15-SB-12
125V, 15 amp, Twist Lock, 6 ft	PC-PP-125-15-TL-6
125V, 15 amp, Twist Lock, 12 ft	PC-PP-125-15-TL-12
125V, 20 amp, Twist Lock, 6 ft	PC-PP-125-20-TL-6
125V, 20 amp, Twist Lock, 12 ft	PC-PP-125-20-TL-12
250V, 20 amp, Twist Lock, 6 ft	PC-PP-250-20-TL-6
250V, 20 amp, Twist Lock, 12 ft	PC-PP-250-20-TL-12
277V, 15 amp, Twist Lock, 6 ft	PC-PP-277-15-TL-6
277V, 15 amp, Twist Lock, 12 ft	PC-PP-277-15-TL-12
277V, 20 amp, Twist Lock, 6 ft	PC-PP-277-20-TL-6
277V, 20 amp, Twist Lock, 12 ft	PC-PP-277-20-TL-12
480V, 20 amp, Twist Lock, 6 ft	PC-PP-480-20-TL-6
480V, 20 amp, Twist Lock, 12 ft	PC-PP-480-20-TL-12
600V, 20 amp, Twist Lock, 6 ft	PC-PP-600-20-TL-6
600V, 20 amp, Twist Lock, 12 ft	PC-PP-600-20-TL-12
600V, Whip, 12ft	PC-PP-600-W-12
Turret Hub Hanger 0.5" Male	1278-5-M
Turret Hub Hanger 0.75" Male	1278-75-M
Turret Hub Hanger 0.5" Female	1275-5-F
Turret Hub Hanger 0.75" Female	1278-75-F

\*All Motion sensor purchases come as a set, including a motion sensor and an L7 Wattstopper lens.

### TURRET ORDERING INFORMATION

SAMPLE ORDER NUMBER: TUR-5-100-40-1-6-1-1-1-X-X-1

SERIES	WATTAGE	KELVIN	OPTICS	LENS	FINISH	DRIVER VOLTAGE	REMOTE CABLE	MOTION SENSOR	BATTERY BACKUP	DLC
TUR-5 High Temp	100- (100W)	40- (4000K)	1- No	6- Flat Tempered Glass Clear	1- Black	1- 120/277V	1- 3'	X- No	X- No	1- Standard
	150- (150W)	50- (5000K)				4- 347/480V	2- 10'	1- Standard*	1- Yes	2- Premium
	200- (200W)						3- 25'	2- Internet of Things*		
	250- (250W)						4- 50'			
	300- (300W)						5-100'			
							6- 150'			
							7- 200'			
							8- 250'			

\* Motion Sensor information: Standard (1) features sensors by Wattstopper with L7 lens. Internet of Things or IOT, (2) features sensors by Enlighted Sensors

\*\* Fixture includes a 6 foot Whip Plug N Play Cord. For additional cord options, please see the Power Cord Table referenced above for ordering information.

3115 N 21<sup>st</sup> Street, Suite 2, Sheboygan, WI 53083  
920-287-3840

tactiklighting.com

