

# Turret Series LED

## High Temperature



### SPECIFICATIONS

Power Factor.....>0.9  
 Input Voltage ..... 120/277V & 347/480V  
 Performance..... Up to 163 lm/W  
 Operational Temperature..... -40°F to 185°F (-40°C to 85°C)  
 Distribution..... 120°  
 Mount Type..... Suspension  
 Available Wattages..... 100W, 150W, 200W, 250W, 300W  
 Kelvin Temperature.....4000K, 5000K  
 Color Rendering Index (4000K) .....>70  
 Color Rendering Index (5000K) .....>90

### FEATURES

- > Up to 185°F (or 85°C)
- > Patent-pending remote driver minimizes fixture operating temperature and allows fixture to evolve with changing plant floor demands with no re-gridding required
- > Inventronics Drivers with less than 1% failure rate
- > Dimmable 0-10V
- > In-series transient voltage surge suppressor (TVSS) protects fixture against failure due to dirty power and power supply surges
- > Includes 10 Year Module Warranty
- > Optional motion sensor. Choose from standard by Wattstopper with L7 lens (fig 1.1 & fig 1.2\*), or Internet of Things (IOT) by Enlighted Sensors (fig 1.3).
- > UL 1598 listed
- > IP65 rated



### LUMINOUS OUTPUT & DIMENSIONS

WATTS	LUMENS	DIAMETER
100 Watts	14,400 lumens	11 inches
150 Watts	22,180 lumens	16 inches
200 Watts	32,730 lumens	16 inches
250 Watts	39,910 lumens	18 inches
300 Watts	49,550 lumens	18 inches

### POWER CORDS & ACCESSORIES

DESCRIPTION	PRODUCT NUMBER
125V, 15 amp, Straight Blade, 6 ft	PC-PP-125-15-SB-6
125V, 15 amp, Straight Blade, 12 ft	PC-PP-125-15-SB-12
125V, 15 amp, Twist Lock, 6 ft	PC-PP-125-15-TL-6
125V, 15 amp, Twist Lock, 12 ft	PC-PP-125-15-TL-12
125V, 20 amp, Twist Lock, 6 ft	PC-PP-125-20-TL-6
125V, 20 amp, Twist Lock, 12 ft	PC-PP-125-20-TL-12
250V, 20 amp, Twist Lock, 6 ft	PC-PP-250-20-TL-6
250V, 20 amp, Twist Lock, 12 ft	PC-PP-250-20-TL-12
277V, 15 amp, Twist Lock, 6 ft	PC-PP-277-15-TL-6
277V, 15 amp, Twist Lock, 12 ft	PC-PP-277-15-TL-12
277V, 20 amp, Twist Lock, 6 ft	PC-PP-277-20-TL-6
277V, 20 amp, Twist Lock, 12 ft	PC-PP-277-20-TL-12
480V, 20 amp, Twist Lock, 6 ft	PC-PP-480-20-TL-6
480V, 20 amp, Twist Lock, 12 ft	PC-PP-480-20-TL-12
600V, 20 amp, Twist Lock, 6 ft	PC-PP-600-20-TL-6
600V, 20 amp, Twist Lock, 12 ft	PC-PP-600-20-TL-12
600V, Whip, 12ft	PC-PP-600-W-12
Turret Hub Hanger 0.5" Male	1278-5-M
Turret Hub Hanger 0.75" Male	1278-75-M
Turret Hub Hanger 0.5" Female	1278-5-F
Turret Hub Hanger 0.75" Female	1278-75-F

\*All Motion sensor purchases come as a set, including a motion sensor and an L7 Wattstopper lens.

### TURRET ORDERING INFORMATION

SAMPLE ORDER NUMBER: TUR-5-100-40-1-2-1-1-1-X-X-1

SERIES	WATTAGE	KELVIN	OPTICS	LENS	FINISH	DRIVER VOLTAGE	REMOTE CABLE	MOTION SENSOR	BATTERY BACKUP	DLC
TUR-5 High Temp	100- (100W)	40- (4000K)	1- No	2- Flat Poly Clear	1- Black	1- 120/277V	X- Integrated Driver	X- No	X- No	1- Standard
	150- (150W)	50- (5000K)		6- Flat Tempered Glass Clear		4- 347/480V	1- 3'	1- Standard*	1- Yes	2- Premium
	200- (200W)						2- 10'	2- IOT*		
	250- (250W)						3- 25'			
	300- (300W)						4- 50'			
						5- 100'				
						6- 150'				
						7- 200'				
						8- 250'				
						9- 500'				

\* Motion Sensor information: Standard (1) features sensors by Wattstopper with L7 lens. Internet of Things or IOT, (2) features sensors by Enlighted Sensors

\*\* Fixture includes a 6 foot Whip Plug N Play Cord. For additional cord options, see Power Cord Table above for ordering information.



# Turret Series LED

## Standard Temperature



### SPECIFICATIONS

Power Factor.....	>0.9
Input Voltage .....	120/277V & 347/480V
Performance.....	Up to 163 lm/W
Operational Temperature.....	-40°F to 125°F (-40°C to 52°C)
Distribution.....	120°
Mount Type.....	Suspension
Available Wattages.....	100W, 150W, 200W, 250W, 300W, 350W, 400W
Kelvin Temperature .....	4000K, 5000K
Color Rendering Index (4000K) .....	>70
Color Rendering Index (5000K) .....	>90

### FEATURES

- > Up to 125°F (or 52°C)
- > Patent-pending remote driver minimizes fixture operating temperature and allows fixture to evolve with changing plant floor demands with no re-gridding required
- > Inventronics Drivers with less than 1% failure rate
- > Dimmable 0-10V
- > In-series transient voltage surge suppressor (TVSS) protects fixture against failure due to dirty power and power supply surges
- > Includes 10 Year Module Warranty
- > Optional motion sensor. Choose from standard by Wattstopper with L7 lens (fig 1.1 & fig 1.2\*), or Internet of Things (IOT) by Enlighted Sensors (fig 1.3).
- > UL 1598 listed
- > IP65 rated



### LUMINOUS OUTPUT & DIMENSIONS

WATTS	LUMENS	DIAMETER
100 Watts	14,400 lumens	11 inches
150 Watts	22,180 lumens	11 inches
200 Watts	32,730 lumens	16 inches
250 Watts	39,910 lumens	16 inches
300 Watts	49,550 lumens	18 inches
350 Watts	57,973 lumens	18 inches
400 Watts	66,050 lumens	18 inches

### POWER CORDS & ACCESSORIES

DESCRIPTION	PRODUCT NUMBER
125V, 15 amp, Straight Blade, 6 ft	PC-PP-125-15-SB-6
125V, 15 amp, Straight Blade, 12 ft	PC-PP-125-15-SB-12
125V, 15 amp, Twist Lock, 6 ft	PC-PP-125-15-TL-6
125V, 15 amp, Twist Lock, 12 ft	PC-PP-125-15-TL-12
125V, 20 amp, Twist Lock, 6 ft	PC-PP-125-20-TL-6
125V, 20 amp, Twist Lock, 12 ft	PC-PP-125-20-TL-12
250V, 20 amp, Twist Lock, 6 ft	PC-PP-250-20-TL-6
250V, 20 amp, Twist Lock, 12 ft	PC-PP-250-20-TL-12
277V, 15 amp, Twist Lock, 6 ft	PC-PP-277-15-TL-6
277V, 15 amp, Twist Lock, 12 ft	PC-PP-277-15-TL-12
277V, 20 amp, Twist Lock, 6 ft	PC-PP-277-20-TL-6
277V, 20 amp, Twist Lock, 12 ft	PC-PP-277-20-TL-12
480V, 20 amp, Twist Lock, 6 ft	PC-PP-480-20-TL-6
480V, 20 amp, Twist Lock, 12 ft	PC-PP-480-20-TL-12
600V, 20 amp, Twist Lock, 6 ft	PC-PP-600-20-TL-6
600V, 20 amp, Twist Lock, 12 ft	PC-PP-600-20-TL-12
600V, Whip, 12ft	PC-PP-600-W-12
Turret Hub Hanger 0.5" Male	1278-5-M
Turret Hub Hanger 0.75" Male	1278-75-M
Turret Hub Hanger 0.5" Female	1278-5-F
Turret Hub Hanger 0.75" Female	1278-75-F

\*All Motion sensor purchases come as a set, including a motion sensor and an L7 Wattstopper lens.

### TURRET ORDERING INFORMATION

SERIES	WATTAGE	KELVIN	OPTICS	LENS	FINISH	DRIVER VOLTAGE	REMOTE CABLE	MOTION SENSOR	BATTERY BACKUP	DLC
TUR-6 Std Temp	100- (100W)	40- (4000K)	1- No	2- Flat Poly Clear	1- Black	1- 120/277V	X- Integrated Driver	X- No	X- No	1- Standard
	150- (150W)	50- (5000K)		6- Flat Tempered Glass Clear		4- 347/480V	1- 3'	1- Standard*	1- Yes	2- Premium
	200- (200W)						2- 10'	2- IOT*		
	250- (250W)						3- 25'			
	300- (300W)						4- 50'			
	350- (350W)						5- 100'			
	400- (400W)						6- 150'			
							7- 200'			
						8- 250'				
						9- 500'				

\* Motion Sensor information: Standard (1) features sensors by Wattstopper with L7 lens. Internet of Things or IOT, (2) features sensors by Enlighted Sensors

\*\* Fixture includes a 6 foot Whip Plug N Play Cord. For additional cord options, see Power Cord Table above for ordering information.

